

## IS- 6517 Interactive Flat Panel



- Zero gap Bonding technology, low parallax writing and wider viewing angles
- 4 mm anti- glare toughened glass with high haze OC for clearer display against ambient light interference
- Light- sensitive brightness adjustment and DC dimming support ( de- flashing) for a more eye-protection display
- 4 K Ultra HD display , support full channel 4K UI display
- Front USB3 .0\*3 + on-board USB3 .0\* 1 , supports switching with channels
- Support for Wireless projection
- $\pm 1$  mm High precision infrared touch control for smooth writing
- Supports dual pens and dual colour displays for easy multi- person collaboration
- Wi-Fi6 support, dual-band 2 .4G/5G, AP+ STA operating mode
- Intelligent wake-up for HDMI/ VGA/ RS2 3 2 channels & network signal input in standby mode
- One network support, Android and OPS both on Gigabit network
- Support network sharing
- Split screen , parallel tasks and wider scenes
- Eye protection, lock screen, touch lock and other tools.

## Product parameters

Panel	LCD Size		6 5 ”
	Type of Panel		ADS
	Respond Time		8ms
	Visual Ratio		16:9
	Max Visual Area		1428.48 (H) ×803.52 (V) mm
	Resolution		3840 (H) ×2160 (V)
	Pixel pitch		0.372×0.372mm
	Frequency		60 Hz
	Display Colors		1.07B (10bit)
	Color saturability		72%
	Contrast ration( Typ)		4000:1
	Viewing Angle		178 °(H/V)
	Light source		DLED
	Camera		48MP Camera Built-in
	Microphone		8 Array
	Brightness		350cd/m2
	Life Span		≥ 50000hrs
Audio- video parameters	Speaker	Soundtrack	2.0
		Power	2 × 15W
Touch parameter	Touch specifications		Non- contact infrared sensing technology
	Support Systems		Windows10/ Windows8/ Windows7/ Windows XP/ Android/Linux/ Mac OS X/ Chrome
	Touch Points		2 0 Points Touch
	Min. Identifier		2 mm
	Input mode		Opaque object ( finger, pen, etc)
	Respond time		≤ 10ms
	Touch depth		± 1mm
	Writing height		≤ 3 mm
	Writing display		Single Stylus pen two- colour
	Output coordinates		32767 (W) × 32767(D)
System	System Version		Android 14.0
	CPU		Cortex A55*8
	GPU		Aem Mall G52*8
	RAM		8 GB
	ROM		128GB
Wireless	Bluetooth	Version	5.0
		Working	
		Frequency	2.4GHz
		Working	
		Distance	0~ 10m

	Wi- Fi	Version	802 . 11ac/b/g/n/a/ax
		Working	2 . 4 GHz/ 5 GHz

		Frequency	
		Working	
		Di stance	0~ 10m
I/ O Interface	HDMI IN	1	
	VGA	1	
	USB 2.0	1	
	USB 3.0	1	
	TOUCH USB	1	
	PC AUDIO IN	1	
	EARPHONE	1	
	RS232	1	
	TF Card	1	
	COAX	1	
	RJ45 IN	1	
	HDMI IN	1	
	Front Interface	USB3.0	3
TOUCH USB		1	
HDMI IN		1	
Type C		1	
Power	Voltage	100 -240V ~ 50/60Hz 4A	
	Max. power consumption	350W	
	Standby power consumption	≤ 0 . 5W	
Structure	Bare dimension	1488.4×896.6×87.2mm	
	Packing dimension	1630×220×1050mm	
	VESA hole site	600×400mm	
	Wall mounting screw specifications	M8×2.5mm	
	Net weight	45KGS	
	Gross weight	56 KGS	
Accessories	Power cord	× 1	
	Stylus pen	×2	
	Wall mount	× 1	
	Operation manual	× 1	
Environment	Working temperature	0℃~40℃	
	Working humidity	10%~90%RH	

	Storage temperature	- 20°C ~ 60°C
	Storage humidity	10%~ 90% RH
	Working Elevation	<5000m

\* Disclaimer

Due to product configuration and manufacturing process, actual body size/ body weight may vary, please refer to the actual

product.

The product images in this specification are for illustrative purposes only. The actual product effect ( including but not limited

to appearance, colour and size) may vary slightly.

Please refer to the actual product.

In order to provide accurate specifications as far as possible, the text expressions and pictures in this specification may be adjusted and revised in real time.

The product specification may be adjusted and revised in order to match the actual product performance and specifications.

In the event that such changes and adjustments are necessary, no special notice will be given.